

**JUMO GmbH & Co. KG**  
Delivery address: Mackenrodtstraße 14  
36039 Fulda, Germany  
Postal address: 36035 Fulda, Germany  
Phone: +49 661 6003-0  
Fax: +49 661 6003-607  
E-mail: mail@jumo.net  
Internet: www.jumo.net

**JUMO Instrument Co. Ltd.**  
JUMO House  
Temple Bank, Riverway  
Harlow, Essex CM20 2DY, UK  
Phone: +44 1279 635533  
Fax: +44 1279 635262  
E-mail: sales@jumo.co.uk  
Internet: www.jumo.co.uk

**JUMO Process Control, Inc.**  
8 Technology Boulevard  
Canastota, NY 13032, USA  
Phone: 315-697-5866  
1-800-554-JUMO  
Fax: 315-697-5867  
E-mail: info@jumo.us  
Internet: www.jumo.us



# JUMO frostTHERM-AT/-DR

## Type 604100, Surface-mounted or DIN Rail Thermostat

### Special features

- **PUSH IN** connection technology • **reduced installation time by 50 %**
- Maximum switching capacity 16 A, 230 V
- Protection type (AT) IP40 - IP65  
(DR) IP20

### Brief description

The frost protection thermostat is used for temperature monitoring in ventilation and air conditioning systems to prevent damage caused by frost. It has a low switching differential and a high reproducibility. Reset occurs automatically (STW) or manually (STB).


High application flexibility and the latest connection technology are the essential equipment features of this thermostat series. The thermostat case is suitable for all common installation types such as wall, pipe, and DIN rail mounting. The JUMO frostTHERM-DR type is a specific variation with a special case bottom section for DIN rail or wall mounting. This allows easy mounting on mounting rails TH35 according to DIN EN 60715 (e.g. in control cabinets). This version considerably reduces the mounting time.

The "Push-In<sup>®</sup>" terminal technology allows the connection wires to be only inserted into the contact point up to the stop. No tool is required for connecting the wire or braid with the ferrule, thereby increasing safety during wiring. As a result, the costs and time required for connection is considerably reduced compared that of the conventional screw terminal.

The "Push-In<sup>®</sup>" terminal technology allows direct switching of loads up to 16 A at 230 V AC. The installation costs can be reduced further because a contactor is not required.



JUMO frostTHERM-AT (STW)



JUMO frostTHERM-DR (STW)

**JUMO GmbH & Co. KG**  
 Delivery address: Mackenrodtstraße 14  
 36039 Fulda, Germany  
 Postal address: 36035 Fulda, Germany  
 Phone: +49 661 6003-0  
 Fax: +49 661 6003-607  
 E-mail: mail@jumo.net  
 Internet: www.jumo.net

**JUMO Instrument Co. Ltd.**  
 JUMO House  
 Temple Bank, Riverway  
 Harlow, Essex CM20 2DY, UK  
 Phone: +44 1279 635533  
 Fax: +44 1279 635262  
 E-mail: sales@jumo.co.uk  
 Internet: www.jumo.co.uk

**JUMO Process Control, Inc.**  
 8 Technology Boulevard  
 Canastota, NY 13032, USA  
 Phone: 315-697-5866  
 1-800-554-JUMO  
 Fax: 315-697-5867  
 E-mail: info@jumo.us  
 Internet: www.jumo.us



## Switching function

<b>Safety temperature monitor STW</b>	If the probe line falls below the entered setpoint value over a length of 15 cm with 3 m, 30 cm with 6 m, and 40 cm with 12 m, then electrical circuit 1-2 is opened while electrical circuit 1-4 is closed due to the change-over function. When the temperature rises, the microswitch is automatically switched back to its original position.  If the measuring system is destroyed (i.e. if the expansion fluid escapes) the pressure in the diaphragm drops and permanently opens electrical circuit 1-2 and closes electrical circuit 1-4.
<b>Safety temperature limiter STB</b>	In the event of a temperature drop, the safety temperature limiter automatically locks and can only be unlocked manually once the temperature has risen again.  If the measuring system is destroyed (i.e. if the expansion fluid escapes), the pressure in the diaphragm drops and permanently opens electrical circuit 1-2 and closes electrical circuit 1-4.

## Technical data

	Type 5	Type 7
<b>Case</b>	Case bottom section: Case lid: ABS with inspection window (PMMA) Color: Cobalt blue RAL 5013	PA (reinforced) Color: Silver gray RAL 7001
<b>Setpoint value adjustment</b> STW, STB	The switching point can be adjusted with a screwdriver once the case lid has been removed. The set switching point can be checked through the inspection glass.	Switching point can be adjusted with a screwdriver.
<b>Protection class</b>	IP 40 according to EN 60529 IP 65 according to EN 60529 (TZ 404)	IP 20 according to EN 60529
<b>Electrical connection</b>	Cable gland M 20 x 1.5, for cable Ø 6-12 mm	Cable connection directly on <b>PUSH IN</b> terminals
<b>Probe line-Ø</b>	Approx. 2.4 mm (or 9.5 mm with 1.8 m capillary)	
<b>Case mounting</b>	Wall mounting / pipe mounting	Wall mounting, DIN rail installation TH35 according to DIN EN 60715
<b>Weight</b>	Approx. 0.2 kg	
<b>Allowable storage temperature</b>	-30 °C to +80 °C	
<b>Allowable ambient conditions on the switching head</b>	-20 °C to +80 °C The ambient temperature must exceed the switching point by +2 °C.	
<b>Maximum allowable probe line temperature</b>	120 °C	
<b>Allowable minimum bending radius of the probe line</b>	20 mm	

## Electrical data

<b>Electrical contact</b>	Snap-action switch with single-pole changeover contact	
<b>Switching capacity</b>	STW	STB
	On the N/C contact (contact deck 1-2): AC 230 V +10 %, 16 (2.5) A, cos φ = 1 (0.6), DC 230 V +10 %, 0.25 A  On the N/O contact (contact deck 1-4): AC 230 V +10 %, 6.3 (2.5) A, cos φ = 1 (0.6), DC 230 V +10 %, 0.25 A	On the N/C contact (contact deck 1-2): AC 230 V +10 %, 16 (2.5) A, cos φ = 1 (0.6), DC 230 V +10 %, 0.25 A  On the signal contact (contact deck 1-4): AC 230 V +10 %, 2 (0.4) A, cos φ = 1 (0.6), DC 230 V +10 %, 0.25 A
<b>Electrical connection</b>	<b>PUSH IN</b> contact (plug-type terminal) "Push-In" terminal technology: Patented connection technology from Weidmüller GmbH & Co. KG, Detmold.	
<b>Connection cross section</b>	0.75 to 2.5 mm <sup>2</sup> finely stranded (single-wire, fine wired with ferrule)	
<b>Switching reliability</b>	To ensure high switching reliability, we recommend a minimum load of: AC / DC = 24 V, 100 mA with silver contacts	
<b>Switching point accuracy</b>	+/- 2 °C	
<b>Switching differential</b>	1.5 +/- 1 °C	

**JUMO GmbH & Co. KG**  
 Delivery address: Mackenrodtstraße 14  
 36039 Fulda, Germany  
 Postal address: 36035 Fulda, Germany  
 Phone: +49 661 6003-0  
 Fax: +49 661 6003-607  
 E-mail: mail@jumo.net  
 Internet: www.jumo.net

**JUMO Instrument Co. Ltd.**  
 JUMO House  
 Temple Bank, Riverway  
 Harlow, Essex CM20 2DY, UK  
 Phone: +44 1279 635533  
 Fax: +44 1279 635262  
 E-mail: sales@jumo.co.uk  
 Internet: www.jumo.co.uk

**JUMO Process Control, Inc.**  
 8 Technology Boulevard  
 Canastota, NY 13032, USA  
 Phone: 315-697-5866  
 1-800-554-JUMO  
 Fax: 315-697-5867  
 E-mail: info@jumo.us  
 Internet: www.jumo.us



Factory setting switching point	5 °C
---------------------------------	------

## Connection diagram

		<p>STW</p>	<p>STB</p>	<p>The connection diagram included in the data sheet provides initial information about the connection options. Only use the installation instructions or the operating instructions for the electrical connection. The know-how and the correct technical implementation of the safety instructions/warnings contained in these documents are prerequisite for the installation, electrical connection, and startup as well as for safety during operation.</p>
--	--	------------	------------	--

## Dimensions

### JUMO frostTHERM type 604100

JUMO frostTHERM-AT					
JUMO frostTHERM-DR					

## Accessories

(Data sheet 606710)

Sales no.	Type	Material	
60/00558731	Holder	Polyamide, reinforced	
3 pieces			
60/00558730			
6 pieces			

**JUMO GmbH & Co. KG**  
 Delivery address: Mackenrodtstraße 14  
 36039 Fulda, Germany  
 Postal address: 36035 Fulda, Germany  
 Phone: +49 661 6003-0  
 Fax: +49 661 6003-607  
 E-mail: mail@jumo.net  
 Internet: www.jumo.net



**JUMO Instrument Co. Ltd.**  
 JUMO House  
 Temple Bank, Riverway  
 Harlow, Essex CM20 2DY, UK  
 Phone: +44 1279 635533  
 Fax: +44 1279 635262  
 E-mail: sales@jumo.co.uk  
 Internet: www.jumo.co.uk

**JUMO Process Control, Inc.**  
 8 Technology Boulevard  
 Canastota, NY 13032, USA  
 Phone: 315-697-5866  
 1-800-554-JUMO  
 Fax: 315-697-5867  
 E-mail: info@jumo.us  
 Internet: www.jumo.us



## Order details

### JUMO frostTHERM type 604100

<b>Order code</b>	<b>(1) Basic type</b>
604100	JUMO frostTHERM with single-pole snap-action switch
	<b>(2) Basic type extension</b>
20	Safety temperature monitor (STW)
70	Safety temperature limiter (STB)
	<b>(3) Type</b>
5	 Surface-mounted thermostat
7	 DIN rail thermostat
	<b>(4) Control / limit value range</b>
140	-10 to +15 STW, STB
	<b>(5) Probe line length</b>
1800	1800 mm Capillary with bulb probe
3000	3000 mm
6000	6000 mm
12000	12000 mm
	<b>(6) Probe diameter</b>
0	Without (for probe line)
9	∅ 9.5 mm (for 1800 mm capillary with cartridge probe)
	<b>(7) Probe material</b>
40	Cu Copper
	<b>(8) Extra code</b>
000	Without extra code
404	Case protection class IP65

**Order code**

(1) (2) (3) (4) (5) (6) (7) (8)  
 604100 / [ ] - [ ] - [ ] - [ ] - [ ] - [ ] / [ ]

**Order example**

604100 / [ 20 ] - [ 5 ] - [ 140 ] - [ 3000 ] - [ 0 ] - [ 40 ] / [ 404 ]

## Stock versions

Sales no.	Type	Control Range °C	Probe lead length	Protection class
60/60003347	JUMO frostTHERM-AT /20	-10 to +15	3000 mm	IP 40
60/60003348			6000 mm	
60/60003349			3000 mm	IP 65
60/60003350			6000 mm	